P1200HD Portable Collector

Specifications



Specifications

Filter Cartridges: (1) Cellulose Flame Retardant Media
Motor/Blower: 1.5 HP, Direct Drive, Backward Incline Blower
Electrical Requirements: 1 Ph: 120v
Air Flow: 1,200 CFM
Built-in Spark Arrestance: (1) 14"x14"x2" Metal Mesh
Silencing: Internal Noise Abatement in Motor/Blower Compartment, 60-74 dBa
Weight: 311 lbs (with Fume Arm)

Blower & Motor

Blower: Backward incline, air foil high efficiency Direct drive, no belts or chains Single phase input power; 1PH: 120V, 60Hz Air Volume: 1,200 CFM

Standard Features

Electrical Enclosure with integrated disconnect switch, motor starter, overload.
Paint: Powder coat finish
Steel Construction: Heavy duty 14 gauge steel
Wheels: (4) swivel {lockable} caster wheels
Filter Cleaning Air Wand included

CLEAN AIR AMERIC/ 866-665-1829

435



8", 7' Arm

Construction: two galvanized steel tubes, three pieces of flex hose at joints, aluminum hood, heavy gauge steel swivel base, and support spring

Components

Collector: Made of powder coated sheet steel **Fume Arm:** Made of steel, aluminum and PVC construction **Delivery design:** Supplied complete with cable and plug

The Clean Air P1200HD Fume Collector features an ergonomic heavy-duty design utilizing strong casters on a portable, easy-to-move collector.

The single-phase 110-120V plug-and-play setup is lightweight but ready to be your go-to mobile source capture for heavy duty maintenance applications.

7 Superior Drive Rome, GA 30161 (866) 665-1829 | (706) 291-1700 www.clean-air.com | sales@clean-air.com



 $\ensuremath{\mathbb{O}}$ 2020 Clean Air America, Inc. *All specifications are subject to change without notice